

PRO TRACK PORTABLE ROADWAY



Heavy duty flooring
for vehicle access

- Stadiums & concerts
- Portable roadways
- Mining industry
- Vehicle access
- Building sites

VEHICLE EXHIBITS



MACHINERY EXHIBITS



CORPORATE EVENTS



PORTABLE ROADS



NON-SLIP TILES



HANGARS



FEATURES

- Heavy duty ground protection
- Tough enough to carry cars, trucks and machinery
- Quick and easy installation
- No ground preparation necessary
- Accommodates uneven ground

USES

- Temporary access roads
- Loading dock areas
- Machinery exhibitions
- Vehicle displays
- Command centres
- Aircraft hangars

INDUSTRIES

- Councils and contractors
- Construction & mining
- Aircraft
- Major events
- Exhibitions
- Circus

TECHNICAL DATA

MATERIAL	HDPE, recyclable. Stable up to 60°C. UV resistant. Flame resistant (B2). Fire rated for internal use by special order.
WEIGHT	2.8kg per tile.
SURFACE AREA	0.27m ² per tile, 3.63 tiles per m ² .
ENVIRONMENT	Biologically and ecologically neutral.
MAXIMUM LOAD	Gravel/sand-based topsoil Cone index (C1) > 100 = 5 tonnes/wheel. Wet pasture Cone index (C1) > 80 = 3 tonnes/wheel.
LOAD FACTOR	Can support compressive loads of up to 2000kPa on firm subsurface.
ENTRY	Chequerplate aluminium ramps available.
EDGING	Aluminium edges available.
INSTALLATION	By hand.
COLOURS	Mid-grey, custom colours available on request at additional cost.
STORAGE	On pallets or metal stacking system.
SHIPPING	On pallets.
SLIP RESISTANCE	AS/NZS 4586: 2004 – Appendix A,B: Dual Classification YF AS/NZS 4586: 2004 – Appendix D: Oil Wet Ramp R10